



go green with **Easy-Read®**

The only thermometers certified
environmentally safe!

- **EnviroKleen™** certified for environmental safety by ChemTel, Inc.
- Non-toxic, non-hazardous, biodegradable black **Enviro-Safe®** liquid.
- **Lead-free** glass and recyclable packaging.
- Accuracy **traceable** to NIST and DKD - statement of accuracy included.
- Individually **serialized** meeting SOP' s and Reportability requirements. (excludes pocket and 200mm lengths)
- **Made in the USA** by H-B, an ISO 9001:2000 company with ISO Guide 17025:2005 laboratory accreditation through A2LA.
- RoHS compliant.

Why Specify **Easy-Read®** ?

- **Easy-Read®** replaces mercury thermometers banned (or partially banned) in more than a dozen US states and many European countries.
- **Easy-Read®** is the ONLY 100% Environmentally safe thermometer on the planet. Liquid is biodegradable and will clean up with soap and water. The glass is lead free and non-toxic.
- **Easy-Read®** meets government, education, and industry mandates to purchase " Green " products.
- **Easy-Read®** can be used wherever spirit (hazardous) or mercury (hazardous) thermometers are being used
- **Easy-Read®** qualifies for H-B' s Mercury Exchange Program. Call 800-4-TEST-LAB for details.
- **Easy-Read®** has lock out specifications. No other thermometer company can meet or exceed these specifications.
- **Easy-Read®** features black **Enviro-Safe®** liquid against yellow back glass - according to studies, this is the most easy to read contrast.
- Manufactured in the USA by a US company, in business since 1903. Meets government requirements for made in the USA product.



www.hbinstrument.com



Sometimes

green

has nothing to do with color...

green thermometers come in black and yellow too!



Easy-Read® Laboratory Thermometers

Range	Division	Accuracy	Immersion	Item No.
200mm (8") Length				
-10 to 110°C	1°	1°	50mm (2")	30591
-10 to 110°C	1°	1°	Total	30592
-10 to 150°C	1°	1°; 1.5° above 105°	50mm (2")	30593
-10 to 150°C	1°	1°; 1.5° above 105°	Total	30594
20 to 230°F	2°	2°	50mm (2")	30597
20 to 230°F	2°	2°	Total	30596
20 to 300°F	2°	2°	50mm (2")	30599
20 to 300°F	2°	2°	Total	30598
297mm (11.69") Length				
-10 to 70°C	0.5°	1°	76mm (3")	30507
305mm (12") Length				
-20 to 110°C	1°	1°	76mm (3")	30505
-20 to 110°C	1°	1°	Total	30500
-20 to 150°C	1°	1°; 1.5° above 105°	76mm (3")	30515
-20 to 150°C	1°	1°; 1.5° above 105°	Total	30510
0 to 230°F	2°	2°	76mm (3")	30535
0 to 230°F	2°	2°	Total	30530
0 to 300°F	2°	2°; 3° above 221°	76mm (3")	30545
0 to 300°F	2°	2°; 3° above 221°	Total	30540
355mm (14") Length				
-10 to 260°C	1°	1°; 1.5° above 105°; 2° above 200°	76mm (3")	30525
-10 to 225°C	1°	1°; 1.5° above 105°; 2° above 200°	Total	30520
20 to 500°F	2°	2°; 3° above 221°; 4° above 392°	76mm (3")	30555
20 to 440°F	2°	2°; 3° above 221°; 4° above 392°	Total	30550

Easy-Read® Pocket Thermometers

Range	Division	Accuracy	Length	Closed Metal Case	Window Metal Case	Window Plastic Case	Aluminum Duplex Case	Window Nickel-Plated Brass Case
-30 to 50°C	1°	1°	160mm (6¼")	30580	30582	—	—	—
-10 to 110°C	1°	1°	160mm (6¼")	30565	30568	—	—	—
-5 to 50°C	0.5°	0.5°	160mm (6¼")	30570	30572	30576	30584	30574
0 to 220°F	2°	2°	160mm (6¼")	30560	30562	30564	—	—
20 to 120°F	1°	1°	160mm (6¼")	30575	30578	—	—	—

