



go green

with

Enviro-Safe[®]

The only thermometers certified
environmentally safe!

- EnviroKleen™ certified for environmental safety by ChemTel, Inc.
- Non-toxic, non-hazardous, biodegradable green **Enviro-Safe[®]** liquid.
- Lead-free glass and recyclable packaging.
- Accuracy traceable to NIST and DKD - statement of accuracy included.
- Individually serialized meeting SOP's and Reportability requirements. (excludes pocket and 200mm lengths)
- Made in the USA by H-B, an ISO 9001:2000 company with ISO Guide 17025:2005 laboratory accreditation through A2LA.
- RoHS compliant.

Why Specify **Enviro-Safe[®]** ?

- **Enviro-Safe[®]** replaces mercury thermometers banned (or partially banned) in more than a dozen US states and many European countries.
- **Enviro-Safe[®]** is the ONLY 100% Environmentally safe thermometer on the planet. Liquid is biodegradable and will clean up with soap and water. The glass is lead free and non-toxic.
- **Enviro-Safe[®]** meets government, education, and industry mandates to purchase " Green " products.
- **Enviro-Safe[®]** can be used wherever spirit (hazardous) or mercury (hazardous) thermometers are being used
- **Enviro-Safe[®]** qualifies for H-B's Mercury Exchange Program. Call 800-4-TEST-LAB for details.
- **Enviro-Safe[®]** has lock out specifications. No other thermometer company can meet or exceed these specifications.
- Manufactured in the USA by a US company, in business since 1903. Meets government requirements for made in the USA product.



www.hbinstrument.com

Form 0-780

green

is not just another

thermometer liquid color...



Enviro-Safe[®] Laboratory Thermometers

Range	Division	Accuracy	Immersion	Item No.
200mm (8") Length				
-10 to 110°C	1°	1°	50mm (2")	20591
-10 to 110°C	1°	1°	Total	20592
-10 to 150°C	1°	1°; 1.5° above 105°	50mm (2")	20593
-10 to 150°C	1°	1°; 1.5° above 105°	Total	20594
20 to 230°F	2°	2°	50mm (2")	20597
20 to 230°F	2°	2°	Total	20596
20 to 300°F	2°	2°	50mm (2")	20599
20 to 300°F	2°	2°	Total	20598
305mm (12") Length				
-20 to 110°C	1°	1°	76mm (3")	20505
-20 to 110°C	1°	1°	Total	20500
-20 to 150°C	1°	1°; 1.5° above 105°	76mm (3")	20515
-20 to 150°C	1°	1°; 1.5° above 105°	Total	20510
0 to 230°F	2°	2°	76mm (3")	20535
0 to 230°F	2°	2°	Total	20530
0 to 300°F	2°	2°; 3° above 221°	76mm (3")	20545
0 to 300°F	2°	2°; 3° above 221°	Total	20540
355mm (14") Length				
-10 to 260°C	1°	1°; 1.5° above 105°; 2° above 200°	76mm (3")	20525
-10 to 225°C	1°	1°; 1.5° above 105°; 2° above 200°	Total	20520
20 to 500°F	2°	2°; 3° above 221°; 4° above 392°	76mm (3")	20555
20 to 440°F	2°	2°; 3° above 221°; 4° above 392°	Total	20550
405mm (16") Length				
-1 to 51°C	0.1°	±1° full scale	76mm (3")	20502
420mm (16½") Length				
-1 to 61°C	0.1°	±1° full scale	76mm (3")	20527
460mm (18") Length				
-1 to 51°C	0.1°	±1° full scale	76mm (3")	20504

Enviro-Safe[®] Pocket Thermometers

Range	Division	Accuracy	Length	Closed Metal Case	Window Metal Case	Closed Plastic Case	Window Plastic Case	Aluminum Duplex Case	Window Nickel-Plated Brass Case
-10 to 110°C	1°	1°	160mm (6¼")	20565	20568	20564	20563	20585	20568B
-5 to 50°C	0.5°	0.5°	160mm (6¼")	20570	20572	20574	20573	20590	20572B
0 to 220°F	2°	2°	160mm (6¼")	20560	20562	20559	20558	20580	20562B
20 to 120°F	1°	1°	160mm (6¼")	20575	20578	20579	20577	20595	20578B

